



Durable Guard 保護罩

Suitable areas 適用範圍

Ideal for cloakrooms, wardrobes, store rooms, bedrooms, bookstores, greenhouses, workshop, etc., etc. for dehumidifying, anti-mould prevention & warmth keeping.

適用於衣帽間、衣櫃、儲物室、睡房、書室、溫室、廠房等等作防潮、抗霉及保溫功能！備有長短尺碼及另有金屬保護罩以配合各類環境需要。

Characteristics 特點

- Save*, durable & space-saving 安全*、耐用及慳地方
- Maintenance-free 無需維修保養
- Easy Installation 安裝簡便
- Wall / Surface-mounted 可掛長或平放
- High efficiency & low operating cost (60W/foot output only) 高效益及低成本(輸出量每呎只需 60W 功率)

Specifications 規格

Model 型號	TH1	TH2	TH3	TH4	TH5	TH6
Loading 負荷	60W	120W	180W	240W	300W	360W
Weight 重量	0.30kg	0.45kg	0.55kg	0.86kg	0.98kg	1.10kg
Length 長度(mm)	308	620	923	1,226	1,575	1,837
Width 闊度	75mm base of mounting bracket 固位腳架底					
Depth 深度	95mm mounted to wall with bracket 鑲牆連架					
O.D. 直徑	~50mmØ					
Voltage 伏特	240V					
Element 成分	Wound nickel/chrome resistance wire on mica frame 採用由燈絲線框所支撐下之開放式螺旋鎳/鉻合金阻抗線					
Case 外殼	Port hole drawn 50mm diameter aluminium tube 50 毫米直徑高質金屬鋁管					
Terminal Cover 末端蓋掩	20% glass filled polypropylene 採用含有百份之 20 玻璃填充聚丙烯					
Case Temp. 外殼溫度	95°C-100°C including ambient 整個範圍介乎 95 度至 100 度之間					
Optional parts 選擇性配件						
Guards 保護網罩	G1S	G2S	G3S	G4S	G5S	-
Length 長 (mm)	370	683	983	~1,283	~1,595	-
Height 高 x Width 闊	~110mm x 155mm					

* - Document of certification complying with BS EN ISO9001:-2000 standard is available from Manufacturer
備有廠方安全檢定文件符合國際 BS EN ISO9001-2000 標準