



Durable Guard 保護罩

**Suitable areas 適用範圍**

Ideal for cloakrooms, wardrobes, store rooms, bedrooms, bookstores, greenhouses, workshop, etc., etc. for dehumidifying, anti-mould prevention & warmth keeping.

適用於衣帽間、衣櫃、儲物室、睡房、書室、溫室、廠房等等作防潮、抗霉及保溫功能！備有長短尺碼及另有金屬保護罩以配合各類環境需要。

**Characteristics 特點**

- Save\*, durable & space-saving 安全\*、耐用及慳地方
- Maintenance-free 無需維修保養
- Easy Installation 安裝簡便
- Wall / Surface-mounted 可掛長或平放
- High efficiency & low operating cost (60W/foot output only) 高效益及低成本(輸出量每呎只需 60W 功率)

**Specifications 規格**

| Model 型號                    | TH1H   | TH2H       | TH3H       | TH4H       | TH5H       | TH6H   |
|-----------------------------|--|------------|------------|------------|------------|--------|
| Loading 負荷                  | 60W  | 120W       | 180W       | 240W       | 300W       | 360W   |
| Weight 重量                   | 0.30kg   | 0.45kg     | 0.55kg     | 0.86kg     | 0.98kg     | 1.10kg |
| Length 長度(mm)               | 308  | 620        | 923        | 1,226      | 1,575      | 1,837  |
| Width 闊度                    | 75mm base of mounting bracket 固位腳架底  |            |            |            |            |        |
| Depth 深度                    | 95mm mounted to wall with bracket 鑲牆連架   |            |            |            |            |        |
| O.D. 直徑                     | ~50mmØ   |            |            |            |            |        |
| Voltage 伏特                  | 240V   |            |            |            |            |        |
| Element 成分                  | Wound nickel/chrome resistance wire on mica frame<br>採用由燈絲線框所支撐下之開放式螺旋鎳/鉻合金阻抗線 |            |            |            |            |        |
| Case 外殼                     | Port hole drawn 50mm diameter aluminium tube<br>50 毫米直徑高質金屬鋁管                  |            |            |            |            |        |
| Terminal Cover 末端蓋掩         | 20% glass filled polypropylene 採用含有百份之 20 玻璃填充聚丙烯                              |            |            |            |            |        |
| Case Temp. 外殼溫度             | 95°C-100°C including ambient 整個範圍介乎 95 度至 100 度之間                              |            |            |            |            |        |
| <b>Optional parts 選擇性配件</b> |  |            |            |            |            |        |
| Guards 保護網罩                 | <b>G1S</b>   | <b>G2S</b> | <b>G3S</b> | <b>G4S</b> | <b>G5S</b> | -      |
| Length 長 (mm)               | 370  | 683        | 983        | ~1,283     | ~1,595     | -      |
| Height 高 x Width 闊          | ~110mm x 155mm   |            |            |            |            |        |

\* - Document of certification complying with BS EN ISO9001:-2000 standard is available from Manufacturer  
備有廠方安全檢定文件符合國際 BS EN ISO9001-2000 標準